



Shakespeare

A valmont.™ BRAND

19845 US Highway 76
Newberry, SC 29108
T: 800-800-9008
F: 803-276-8940
www.skp-cs.com

STRAIGHT SQUARE COMPOSITE POLES



**COMPOSITE
TUFF-POLE®**

Straight Square Composite Poles offer a unique solution to today's demanding requirements for lighting standards that enhance design. Their contemporary look is favored by architects, engineers and planners.

BENEFITS

- Ease of installation
- Lightweight for easy handling
- Will not rust, rot or corrode
- Dent resistant
- Non-conductive

4" SQUARE SS4A AND SS4B SERIES	5" SQUARE SS5A AND SS5B SERIES
(Anchor Base and Direct Burial)	(Anchor Base and Direct Burial)
<ul style="list-style-type: none"> ● 4" x 4" Straight Square ● Mounting Heights to 25' ● Smooth Finish ● Multiple Color Options ● Tenon Top or Capped for Side Drilling ● Anchor Bolts Included (5/8" x 21" x 3") ● Base Cover Included ● 8" - 12.5" Bolt Circle 	<ul style="list-style-type: none"> ● 5" x 5" Straight Square ● Mounting Heights to 30' ● Smooth Finish ● Multiple Color Options ● Tenon Top or Capped for Side Drilling ● Anchor Bolts Included (3/4" x 30" x 3") ● Base Cover Included ● 10" - 12.5" Bolt Circle



Shakespeare

A valmont BRAND

19845 US Highway 76
 Newberry, SC 29108
 T: 800-800-9008
 F: 803-276-8940
 www.skp-cs.com

SS4: Straight Square Composite Pole 4" Profile						Anchor Base (SS4A-)		Direct Burial (SS4B-)	
Anchor Base (A) or Direct Burial (B)	Mounting Height (ft)	Effective Projected Area (sq ft)				Anchor Base		Direct Burial	
		90 MPH	100 MPH	110 MPH	120 MPH	Bolt Hole Circle (in)	Weight (lbs)	Shaft Length (ft)	Weight (lbs)
SS4_ - 10	10'	21.5	17.0	13.7	11.1	8" - 12.5"	27#	13'	28#
SS4_ - 15	15'	12.9	9.8	7.5	5.7	8" - 12.5"	37#	19'	40#
SS4_ - 20	20'	7.4	5.2	3.5	2.3	8" - 12.5"	47#	25'	55#
SS4_ - 25	25'	3.8	2.1	0.8	-	8" - 12.5"	57#	30'	70#

SS5: Straight Square Composite Pole 5" Profile						Anchor Base (SS5A-)		Direct Burial (SS5B-)	
Anchor Base (A) or Direct Burial (B)	Mounting Height (ft)	Effective Projected Area (sq ft)				Anchor Base		Direct Burial	
		90 MPH	100 MPH	110 MPH	120 MPH	Bolt Hole Circle (in)	Weight (lbs)	Shaft Length (ft)	Weight (lbs)
SS5_ - 15	15'	28.7	22.1	17.3	13.6	10" - 12.5"	99#	19'	97#
SS5_ - 20	20'	17.5	12.7	9.2	6.5	10" - 12.5"	125#	25'	123#
SS5_ - 25	25'	10.2	6.5	3.8	1.7	10" - 12.5"	150#	30'	154#
SS5_ - 30	30'	5.0	2.0	-	-	10" - 12.5"	176#	35'	180#

Product improvements may be made without prior notice.

- Reduced Lead Time (higher quantities may require longer lead time, consult factory)
- 30' Poles require shipment by flatbed and will ship first available flatbed.
- Freight Allowed \$2,000.00, Prepaid & add under \$2,000.00 SS4A and SS5A
- Include anchor bolts and base cover
- SS4A and SS5A - Pre-Shipped Anchor Bolts are prepaid and add
- Standard colors are Black, Bronze, and Grey
- Standard tenon sizes are 2 3/8" and 3"
- For cut down poles use full length pole price (Ex. SS5A-22 use SS5A-25 price)
- Contact factory for pricing regarding options or modifications
- Advise Size, Location and Orientation of Drilling Requirements (Ref. Drawing)

