

Job Name: _____	Client Name: _____
Job Location - City: _____ State: _____	Created By: _____ Date: _____
Product: _____ Quote: _____	Customer Approval: _____ Date: _____

FEATURES

- Aesthetically pleasing for lighting applications
- Modular construction utilizing high quality aluminum and extruded components
- Lightweight, slip-over design for theft deterrent
- Seamless, clean appearance
- Long-lasting finish available in a variety of colors



POLE BASE DIAMETER RANGE		DIMENSIONS OF BASE COVER			MODEL NUMBER
TAPERED 0.14"/FT (IN)	NON-TAPERED (IN)	DIA (IN)	HEIGHT (IN)	QTY OF ACCESS DOORS	
5.13 - 5.75	4.88 - 5.50	17.00	23.00	0	2C01AO

All dimensions shown are nominal.

PRODUCT ORDERING CODES

MODEL NUMBER	COLOR*	POLE BASE OD (IN)	BASE PLATE			ANCHOR BOLTS		HANDHOLE			
			BOLT CIRCLE DIA (IN)	SQUARE (IN)	THICKNESS (IN)	DIAMETER (IN)	PROJECTION (IN)	SIZE W x H (IN)	CENTER LINE HEIGHT (IN)	PROJECTION (IN)	
2C01AO											
	STEEL WH = White ST = Sandstone BK = Black SM = Silver Metallic SL = Silver LG = Light Gray SG = Slate Gray DT = Dark Tan MB = Medium Bronze CB = Bronze DB = Dark Bronze BN = Brown HG = Hunter Green DG = Dark Green RD = Red SC = Special Color (Contact Factory)	ALUMINUM DWH = White DSS = Sandstone BR = Burgundy HG = Hunter Green DNA = Natural Aluminum DCG = Charcoal Gray DMB = Medium Bronze SBN = Sanded Brown DNB = New Dark Bronze DDB = Dark Bronze SBK = Sanded Black DBL = Black DSB = Steel Blue DTG = Dark Green DBR = Red SC = Special Color (Contact Factory)	1. Model Number, Color and Pole Base OD required on all orders. 2. Additional information required when ordering separate from poles.								

* Choose steel or aluminum when used in conjunction with the appropriate pole material.

HAWTHORNE AO1

Aluminum Components - Slip-Over



STRUCTURES

Job Name: _____	Client Name: _____
Job Location - City: _____ State: _____	Created By: _____ Date: _____
Product: _____ Quote: _____	Customer Approval: _____ Date: _____

BASE COVER CLOSE-UP



SPC7246 04/09 valmontstructures.com carries the most current spec information and supersedes these guidelines.