

Job Name: _____	Client Name: _____
Job Location - City: _____ State: _____	Created By: _____ Date: _____
Product: _____ Quote: _____	Customer Approval: _____ Date: _____

FEATURES

- Aesthetically pleasing for lighting applications
- Durable, high quality aluminum casting provides clean, crisp details
- Slip-over design for theft deterrent
- Provided with stainless steel hardware
- Tamper proof hardware is available as special order
- Long-lasting finish available in a variety of colors



POLE BASE DIAMETER RANGE		DIMENSIONS OF BASE COVER			MODEL NUMBER
TAPERED 0.14"/FT (IN)	NON-TAPERED (IN)	DIA (IN)	HEIGHT (IN)	QTY OF ACCESS DOORS	
5.88 - 6.00	5.75 - 5.88	14.38	12.00	1	1Q01AO

All dimensions shown are nominal.

PRODUCT ORDERING CODES

MODEL NUMBER	COLOR*	POLE BASE OD (IN)	BASE PLATE			ANCHOR BOLTS		HANDHOLE		
			BOLT CIRCLE DIA (IN)	SQUARE (IN)	THICKNESS (IN)	DIAMETER (IN)	PROJECTION (IN)	SIZE W x H (IN)	CENTER LINE HEIGHT (IN)	PROJECTION (IN)
1Q01AO										

STEEL

WH = White
ST = Sandstone
BK = Black
SM = Silver Metallic
SL = Silver
LG = Light Gray
SG = Slate Gray
DT = Dark Tan
MB = Medium Bronze
CB = Bronze
DB = Dark Bronze
BN = Brown
HG = Hunter Green
DG = Dark Green
RD = Red
SC = Special Color
(Contact Factory)

ALUMINUM

DWH = White
DSS = Sandstone
BR = Burgundy
HG = Hunter Green
DNA = Natural Aluminum
DCG = Charcoal Gray
DMB = Medium Bronze
SBN = Sanded Brown
DNB = New Dark Bronze
DDB = Dark Bronze
SBK = Sanded Black
DBL = Black
DSB = Steel Blue
DTG = Dark Green
DBR = Red
SC = Special Color
(Contact Factory)

1. Model Number, Color and Pole Base OD required on all orders.
2. Additional information required when ordering separate from poles.

* Choose steel or aluminum when used in conjunction with the appropriate pole material.

LIBERTY AO1

Cast Aluminum - Slip-Over



STRUCTURES

Job Name: _____	Client Name: _____
Job Location - City: _____ State: _____	Created By: _____ Date: _____
Product: _____ Quote: _____	Customer Approval: _____ Date: _____

BASE COVER CLOSE-UP



SPC7271 04/09 valmontstructures.com carries the most current spec information and supersedes these guidelines.