




The Exceptionally strong, braggably economical Tuff-Top[™] Pole Extension

Unparalleled strength, unmatched economy.

- Exclusive: Filled with structural foam for strength and insect exclusion
- Available in a range of strength ratings
- Light weight, easily installed
- Unexcelled strength, high load capacities
- Adjustable 6" to 10" for pole diameter (19" to 31" circumference)
- Aesthetically pleasing, extends any pole–wood, composite, etc., with or without drilling holes in the top of the pole.


Shakespeare Composite Structures' Tuff-Top Pole Extensions provide a convenient, inexpensive, and durable way to add conductors or increase clearance on an existing pole installation, whether composite or other type of pole. These strong, attractive extensions are factory assembled from a length of fiberglass reinforced composite pole, plus a versatile attachment bracket.

The pole sections are **filled with a durable, permanent, structural foam** that excludes insects and water and discourages flexing. The versatile attachment brackets either bolt through the pole or, for strongest applications, clamp on. Either way, you can add one or more crossarms, as well as a ridge pin and other attachments. The pole sections come in three standard colors, or you can specify.



Tuff-Top Test Data

	Ultimate Load	
Series	(lbs @ 31")	(ft/lbs @ 31")
PTS	5,500	14,208
PTH	6,500	16,790
PTX	8,500	21,958
PTR	8,500	21,958







How to order


The Tuff-Top Pole Extension ordering logic is shown at right. Use this checklist and the diagram above to specify the product you need. If you need assistance, just call.

	Standard	Specify
Series	S (Std)	
Attachment type	B (bolt through)	
Length	54"	
Color	Dark Bronze (5)	
Cap type	C (Cap only)	
Drilling Pattern	UD (undrilled)	
Dia. of drilled holes	11/16"	
Other		




19845 U.S. Highway 76 · Newberry, SC 29108 803.276.5504 · F/803.276.8940

Toll-free in U.S.A.: 1.800.800.9008 · www.skp-cs.com



Shakespeare Tuff-Top Pole Extensions



*Standard Length = 54"; Custom lengths available Weight of standard unit: 72 lbs.

